


Design Floors



TRANSFORM AND IMPRESS




# Moduleo® Our range at a glance

### Wood



Tile





# Redefining benchmarks in flooring.

Changing the way you work, the way you think and perhaps most importantly, changing the way the world sees you. We help businesses change from the floor up, creating remarkable spaces that work hard and look spectacular. It's also what drives us forward; always looking for new ways to make our products better, and make them in a better way.

Change begins with a single step; a step onto Moduleo® design floors.

- 4 About us
- 6 Ecological responsibility
- 8 Retail
- 10 Hospitality and leisure
- 12 Office
- 14 Housing
- 16 Education
- 18 Health and care
- 20 Moduleo® Transform
- 56 Moduleo® Impress
- Joint strips and laying patterns
- 70 Design and development
- 72 Composition and installation
- 74 Technical information

# Changing the face (and floors) of business

Moduleo® is the next generation of luxury flooring, combining the look, feel and durability of real, natural materials, but with the straightforward installation and maintenance associated with vinyl flooring.

moduleo

Design Floors by

Moduleo<sup>®</sup> is brought to you by the IVC Group, a company with a rich and long heritage of producing beautiful, resilient flooring for almost any application.

Based in Belgium, Moduleo® is made at our unique 'green' factory in Avelgem, which was purpose built to manufacture our flooring in a responsible way. A fully automated warehouse facility on site also has the capacity to store 1,000,000m² of Moduleo® flooring.

Besides the numerous energy saving and waste reduction measures in place, our plant also ensures that unlike other manufacturers, we 'own' the entire design,

manufacture and logistics process, without the need to import material from external suppliers. This allows us to retain total quality control at every stage of the journey.

### A complete flooring solution

The versatility of an entire family of IVC brands means that we are able to offer the commercial world the convenience of a one-stop flooring solution to suit all areas of a project.

The product portfolio consists of **4 brands**: Leoline® (residential vinyl floors in rolls), Flexitec® (residential vinyl floors in rolls in North America), Itec® (project vinyl floors in rolls) and Moduleo® (high-quality

modular vinyl floors for project and residential use).

Since 2015 IVC Group forms part of the American listed Mohawk Industries Inc., the world's market leader in flooring.





# Change for the better

At Moduleo®, we are acutely aware of the impact of our operations and are committed to changing the manufacturing of luxury vinyl floors, by leading the way in ecological responsibility.

By choosing Moduleo® flooring for your project, you're choosing a floor that will only make an impact on design spaces, not the planet.



### **Production with green energy**

Our production facility in Avelgem is equipped with three wind turbines that fulfill the strictest health and safety standards for noise and visual pollution. The turbines can operate at up to 13.3 GWh/year and fulfill one third of the energy needs of the plant.



### Strict raw material checks

Moduleo® consciously opts for production processes that meet the international standards. All suppliers must comply with the REACH regulations.



### **Made in Belgium**

All Moduleo® design floors are made in Belgium. By siting our production as close as possible to our customers we avoid the need for environmentally damaging long haul transport.

That's a deliberate choice of ours, to minimise CO<sub>2</sub> emissions and our ecological footprint.







**Sector** Retail

Client Computer Home, Luxembourg

**Situation** As a store specialising in PC and Mac computers, the store required a modern look and as an Apple retailer, a certain aesthetic quality is expected. The store was expecting high footfall, yet a calming ambience is desirable.

Solution

Moduleo® Transform Click Classic Oak and Xtrafloor underlay

Classic Oak is the perfect choice to provide an attractive, yet understated foundation to the retail environment. The 0.55mm wear layer and Protectonite® PU coating means that the flooring can stand up to many years of busy commerce and still look its best.

The Click installation allows the store to retain a level of flexibility to accommodate layout changes.









**Sector** Hospitality and leisure

**Client** Bowlingbaan Scheveningen,

Netherlands

**Situation** Bowlingbaan Scheveningen is one of

the largest bowling centres in the Netherlands, and is home to The Hague Bowling Association, disco bowling, amateur bowling and numerous parties. The nature of the events meant they required a maintenance friendly, durable

floor with a natural appearance.

**Solution** Moduleo® Transform Latin Pine

Moduleo®'s sound insulating properties were key in this application where a high level of ambient noise is already present. This along with the rustic effect of Latin Pine lends a welcoming and attractive space for all visitors. The ease of maintenance of Moduleo® was a key benefit, while the waterproof top layer and R10 slip rating ensure that the alleys are the only slippery surface at Bowlingbaan Scheveningen.







The stunning designs in the range also mean that clients and customers get a fantastic first impression, while the durability of Moduleo® flooring means that it can stand up to the demands of high traffic areas with ease.



**Sector** Office

**Client** Randstad, Belgium

**Situation** Randstad is one of the major HR

service providers in Belgium, specialising in temporary employment,

recruitment and selection,


outplacement, training, in-house offices, HR and project sourcing. It is also the

largest employer in Belgium.

**Solution** Moduleo® Transform Verdon Oak

Randstad wanted to unify its workforce in new offices rather than have staff in many locations. The modern design of Moduleo® Verdon Oak and the extreme durability of the product ensures high

long-term performance.







Thermal performance is also an added benefit for housing, helping to reduce energy consumption, while the choice of designs in the range ensures that residents have an inspirational start to their living space.



**Sector** Housing

**Client** Sleeperdorm, UK

**Situation** Sleeperdorm is a modern hostel based


in the heart of Newcastle. Offering contemporary budget accommodation in communal and private rooms, key considerations included a natural look, performance and price. Sleeperdorm wanted a realistic, hard wearing and easy maintainable floor covering to be used in high traffic areas in a new hostel style hotel. The product had to be fresh and minimalistic.

**Solution** Moduleo® Transform Baltic Maple

The minimalist effect of Baltic Maple added to the contemporary style of the hostel, providing a stylish place to sleep. A comfortable night's sleep is aided by the acoustic properties of Moduleo®, while the durable wear layer means that furniture and footfall have minimal impact. Ease of cleaning is a major benefit, helping to maintain a clean and hygienic environment.







# Education

An environment that is conducive to learning is one that is quiet, clean and inspiring. Moduleo® floors have these qualities in abundance. Sound insulation dampens the noise of everyday school or college life, while the safety of young people is ensured with R10 slip ratings, even in areas liable to spillages such as toilets or changing areas.

A healthy environment can also be maintained as Moduleo® does not harbour dust mites or any other allergens, while the scuff and scratch resistant coverings are handy in spaces where desks and chairs are constantly on the move.



**Sector** Education

**Client** Erasmus school De Pinte, Belgium

**Situation** Floor coverings in schools must meet

very strict requirements. They must be robust, durable, warm, comfortable and hygienic. Also, student and staff


safety is paramount.

**Solution** Moduleo® Transform Concrete

Moduleo® Transform Latin Pine

Available in different colours for a pleasant learning environment, Moduleo® has the perfect combination of high wear layer, compact construction height and slip resistance (R10) to ensure maximum service life. Moreover, floors from the Moduleo® collection are very easy to clean thanks to the revolutionary

PU Protectonite® wear layer.







Any healthcare building should be a place that promotes comfort and wellbeing, not to mention ensuring the safety of its patients. The way that Moduleo® floors does not harbour dust alongside its easy clean properties, make it an ideal choice to maintain a bacteria free environment, while the sound absorption qualities contribute to a calming space.

Care and recovery is not just about practical matters. An aesthetically pleasing environment can be very therapeutic, so the array of elegant designs offered by Moduleo® is perfect for communal areas and for private care spaces.



**Sector** Health and care

**Client** Brühler Turnverein, Germany

**Situation** A busy gym and rehabilitation

centre required a multi-purpose flooring with multiple benefits. Durability was a key factor, due to heavy equipment being used, while maintaining a calm environment for

recuperation was essential.

**Solution** Moduleo® Transform Classic Oak

The Click installation method allowed for minimum disruption to staff and patients, ensuring care levels were not compromised. Additional Xtrafloor underlay was used for improved acoustics, while the Transform wear layer gives protection from heavy loads and sliding movements of fitness equipment. The unique Protectonite® coating also maintains a hygienic environment, free from dirt and scratches.





# **Moduleo® Transform**

# Transform by name, transform by nature.

This hardwearing vinyl flooring solution is a perfect blend of quality and performance. Its 0.55mm wear layer makes Moduleo® Transform ideal for commercial use, even in high traffic environments. With a 10-year warranty, this range aims to transform interiors for the long run.

### **KEY FACTS**

- ▶ 42 wood designs
- ▶ 21 tile designs
- Dryback and Click
- ▶ 10-year commercial warranty











# Baltic Maple





# Blackjack Oak











# Classic Oak



# Cotton













# Country Oak





# Eden Walnut











## Ethnic Wenge





# Fazino Maple







Metallic effect on all products









### Latin Pine



### Montreal Oak













### Persian Walnut



# Verdon Oak














### Azuriet





## Concrete













### Jura Stone



### Steelrock







Metallic effect on all products









### Zeera Slate



### **Moduleo<sup>®</sup> Impress**

## Change you can really feel

The name of our latest collection immediately makes clear what the collection represents: a truly unique impression. The 'embossed in register' procedure contributes to the true-to-nature look and feel of all the Moduleo® Impress floors. With a wear layer of 0.55 mm, this collection is perfect for commercial applications where real impact is needed.

### **KEY FACTS**

- > 22 Unique patterns
- ▶ Embossed in register
- Dryback and Click
- ▶ 15-year commercial warrantv







### Castle Oak











### Country Oak



## Eastern Hickory





High Gloss finish










### Mountain Oak



### Scarlet Oak









### Joint strips 30 strips / box

Moduleo® joint strips are individually coloured to complement our range of flooring. The strips can be used to imitate the use of a grout finish or add sophistication to wooden execution.



### Laying patterns


Create distinctive, unique looks for commercial projects by utilising either standard size options or our special patterns.




Herringbone 196mm x 1320mm




**Herringbone** (customisation) 94mm x 282mm




Brick formation 196mm x 1320mm



Deck formation 196mm x 1320mm Joint strip 4mm x 914mm




Straight lay 196mm x 1320mm




**Wood block** (customisation) 94mm x 282mm



**45° angle** 329mm x 659mm



Straight lay 493mm x 493mm



Brick bond 329mm x 659mm Joint strip 4mm x 9140mm



# Design and development

Using the very latest in CAD/CAM software, our designers take pride in creating virtually flawless reproductions of natural materials. We involve our customers in the creative process and keep close tabs on ever-changing trends in the market.

Our global knowledge and unmatched design expertise makes us the ideal partner for any commercial project. With a dedicated commercial sales team offering practical help and support, we're able to provide a speedy, flexible service.

With personalised commercial flooring and custom made solutions also available, our products can be as individually tailored as our service. A commercial website platform and the fact that we manage the entire design and manufacturing process from our base in Belgium also means a fast turnaround, ensuring you get the product you need exactly when your project needs it.



To ensure our floors are the very best they can be and to give you the confidence of choosing the very best for your commercial project, we have a stringent system of testing and quality assurance. A series of rigorous tests conducted in our plants make sure our customers get the quality products they deserve.

### Our tests include:

- Crack resistance testing
- Delamination testing
- Indentation testing
- Castor chair testing
- Dimensional stability and curling
- Furniture leg testing
- ▶ Ramp test for slip resistance
- Pendulum test for slip resistance
- Surface roughness testing
- Thickness and wear thickness testing











### Functional highlights

### **Hygienic and** easy to clean

No expensive cleaning agents are required to keep your floor at its best; just a simple broom, mop and vacuum cleaner. A Moduleo® floor will not harbor dust mites or other allergens.

### **Protectonite® PU Protection**

Each floor tile is protected with a Protectonite® PU: Extra Polyurethane layer, which protects the floor against scratches and dirt, offering maximum protection with minimum maintenance.

### **Heatinsulation**

Excellent heat insulation means that Moduleo® flooring feels warm to the touch and can even help reduce energy consumption. It can be used in conjunction with underfloor heating.

### Slip and impact resistance Protect yourself, your employees

and the public with Moduleo®. Our floors have undergone considerable tests in critical conditions using both the pendulum and ramp method of slipresistant testing, consistently proving to be a safe solution with a slip rating of R10.

### **Sound resistant**

Unlike traditional wood or laminate flooring, Moduleo® flooring absorbs sound thanks to a soundproof base, giving better acoustics in your spaces and minimizing unwanted noise in high traffic areas.

### **Moisture-proof**

An easy clean, moisture-proof wear laver makes Moduleo® flooring hygienic and suitable for areas that may be subject to spillages.

### Design highlights

### Natural look and feel

By using an embossing cylinder, the top layer of the tiles feature a relief that accurately recreates the subtle textures of natural materials, allowing you to feel wood grains and stone grooves.

### Rovol

The bevel accentuates the Moduleo® planks and tiles, contributing to the natural appearance of your floor.

### **Clear print**

A unique printing technique, using a very fine dot screen, allows for such high resolution that it's almost impossible to tell the difference from the real thing.

### **Minimal shrinkage** or expansion

Thanks to their patented construction with a double fibreglass membrane, all Moduleo® Design Floors have extremely high dimensional stability.

### **Guaranteed quality**


For your peace of mind, Moduleo® commercial floors come with a 10-year commercial warranty.

### **Extra long**

Moduleo® goes to great lengths to ensure every floor will be unique and will retain that natural look.

### Extra large design

More natural variation and less repeating of the same patterns. Our bestseller format has no fewer than 90 unique planks per design, which represents over 23m<sup>2</sup>.



Standard design 1x1m

Moduleo® design 2x1.5m

# The make-up of Moduleo®

The Moduleo® range comprises both planks and tiles that stand out due to their rigidity, ease of maintenance and natural appearance.

The multi-level format has been refined to offer the very best in durability, while our unique manufacturing processes allow us to better recreate the delicate and random patterns found in natural wood and stone. They all combine to give the ultimate in performance and aesthetic quality.





### Installation

### Moduleo<sup>®</sup> is a flexible solution in many ways, not least in its method of installation.

The planks and tiles can either be glued down in the traditional dryback manner, or fixed using the quick and easy Click system. Comprehensive installation information can be found at moduleo.co.uk

### **Dryback**

This is the worldwide standard installation method for luxury vinyl flooring, where the product is securely and permanently glued to the subfloor.

When used with a suitable leveling compound and high quality adhesive, it offers the best results and a cost-effective fixing solution. Dryback offers the opportunity to mix and match products for greater design flexibility.

### Click

Particularly useful in short-term applications or in projects with tight timescales, Click with LockXpress technology is the quick and easy way to install a Moduleo® floor.

Each piece slots directly into place, giving the same stunning aesthetic qualities as traditional installation, but faster and without the need for glue.

LockXpress® is an enhanced vertical locking system that ensures a solid installation and is twice as strong as conventional systems, outperforming other comparable products.



	DRY BACK	LockXpress [LXP]*
	DRYBACK	CLICK
Features & benefits	Best product /price proposition • Design opportunities, mix & match	Easy to install Fast installation
Thickness	2.50 mm	4.50 mm
How to install	Adhesive	Floating with patented Click system
Moduleo® USP	<b>Double glass fibre:</b> best dimensional stability in the market	Double glass fibre: best dimensional stability in the market. Enhanced click system: 2x stronger vertical locking system

Thermal resistance R

Acoustic insulation

Underfloor heating

Stain resistance

Light fastness

Tiles

Castor chair resistance

Electrostatic performance Fomaldehyde group

### Moduleo Transform & Impress

DRY Product Information				
Level of use	EN ISO 10874	23 - 33 - 42		
Total thickness	EN ISO 24346	2.50mm		
Wear layer	EN ISO 24340	0.55mm		
Wear layer PUR treatment		Protectonite®		
Total weight g/m²	EN ISO 23997	4,059		
Size and Packing				
Planks A	EN ISO 24342	196mm x 1320mm	14 pcs/box	3.62m²/box
Planks B	EN ISO 24342	246mm x 1498mm	10 pcs/box	3.69m²/box
Tiles A	EN ISO 24342	329mm x 659mm	16 pcs/box	3.47m²/box
Tiles B	EN ISO 24342	493mm x 493mm	14 pcs/box	3.40m²/box
Test Results				
Inflammability	EN 13501	BfI-S1		
Scratch resistance	EN 660-2	Class T		
Squareness and straightness	EN ISO 24342	≤ 0.25 mm (Tiles B) / ≤ 0.35 mm (Planks A, B and Tiles A)		
Slip Resistance				
onp resistance	DIN 51130:2010	BS 7976-2:2002		
	Ramp method	Pendulum test		
	namp metriod	Dry (PTV's)	Wet (PTV's)	
Embossing 22	R9	69	35	
Embossing 24	R10	61	34	
Embossing 46	R10	67	33	
Embossing 28	R10	64	29	
Embossing 36	R10	67	32	
Embossing 40	R10	67	34	
Embossing 20	R10	59	30	
Embossing 50	R10	66	29	
Embossing 54	R10	59	31	
Embossing 55	R10	66	30	
Embossing 56	R10	52	27	
Embossing 57	R10	60	32	
Residual indentation	EN ISO 24343-1	Norm: ≤ 0.10mm Averag	e result measured: 0.	03mm
Furniture leg resistance	EN ISO 16581	No cracks, no damage		
Curling	EN ISO 23999	≤ 2mm		
Electrical resistance	EN 1081	≤ 10° Ohm		
Dimensional stability	EN ISO 23999	Norm: ≤ 0.25 % Average result measured: ≤ 0.05%		
J	EN 12524	0.05 // //)		

Warranty		10 years commercial		
Product Information				
Level of use	EN ISO 10874	23 - 33 - 42		
Total thickness	EN ISO 24346	4.50mm		
Wear layer	EN ISO 24340	0.55mm		
Wear layer PUR treatment		Protectonite®		
Total weight g/m²	EN ISO 23997	7,681		
Size and Packing				
Planks A	EN ISO 24342	191mm x 1316mm	7 pcs/box	1.76m²/box
Planks B	EN ISO 24342	241mm x 1494mm	6 pcs/box	2.16m <sup>2</sup> /box

0.25w/(m.K)

Very good

Suitable, max 27°C

324mm x 655mm

E1

4dB

≥ 6

0.0100m<sup>2</sup>.K/W

No damage to wearlayer, no delamination

7 pcs/box

1.49m<sup>2</sup>/box

		·	
Test Results			
Inflammability	EN 13501	BfI-S1	
Thermal resistance R	EN ISO 12664	0.0159m².K/W	
Fomaldehyde group	EN 717-1	E1	
For other test results, please see above.			



The warranty covers manufacturing defects and premature wear in the event of normal use.

EN 12524

EN 1815

EN 717-1

EN 140-8

EN ISO 26987

EN ISO 24342

ISO 105 B02

EN 12524

EN 425

EN ISO 12664

### Adhesives

### **Xtrafloor PS adhesive**

is a fast-drying, solvent free co-polymer dispersion adhesive for resilient floorcoverings. It can be used as a wet lay, semi wet or pressure sensitive adhesive for securing PVC floor tiles.

Xtrafloor PS can be applied to a wide range of subfloors including power floated concrete, terrazzo, granolithic, sand/ cement screeds and timber floors.

Floor surfaces must be suitably prepared: sound, dry (<75%RH and incorporate an effective damp proof membrane) and free from contaminants that may prevent adhesion.

Sound asphalt must be skimmed with a minimum of 3mm of an appropriate smoothing underlayment.

### **Xtrafloor HTA adhesive**

is a solvent free, low emission, co-polymer based adhesive for bonding PVC floor tiles. It is particularly suitable for use in conservatories and other areas subject to high temperatures. It is protected against bio-degradation and is suitable for use over normal underfloor heating.

Xtrafloor HT can be applied to a wide range of subfloors including power floated concrete, terrazzo, granolithic, sand/ cement screeds and timber floors.

Floor surfaces must be suitably prepared: sound, dry (<75%RH and incorporate an effective damp proof membrane) and free from contaminants that may prevent adhesion.

Sound asphalt must be skimmed with a minimum of 3mm of an appropriate smoothing underlayment.

### LRV Ratings

### **LRV Ratings**

LRV is defined as the amount of light reflected from a specific product (the proportion of visible light reflected by a surface compared to the sensitivity to light of the human eye).

All of IVC's products have been tested according to BS8493:2008+A1:2010. The LRV values are expressed on a scale of 0-100.

A result of 0 is a surface that perfectly absorbs all light (assumed to be totally black) and 100 which is perfectly reflective (and can be considered totally white).

A lot of resilient floors are made of combinations of different colors. In these cases, Light reflection values are average values based on a large area of the pattern.



































